



## StowAway Cargo Rack License Plate Kit Instructions (020.75)

### Parts Included:

- License Plate Kit Assembly – Pre-wired
- 2 – Screws 10-24 x 3/4" Screws
- 2 - 10-24 Square Nuts
- 5 - Cable Ties

### Tools Needed:

- Phillips Screwdriver

**[www.StowAway2.com](http://www.StowAway2.com)**

**800-943-5377**

## StowAway Cargo Rack License Plate Kit Instructions:

1. Mount the license plate kit assembly to your rack using two of the enclosed cable ties.
2. Route the wiring directly beneath the cargo rack, along the bent section of the frame, then along the stinger to your vehicle's trailer light electrical connector. Use three more cable ties to fasten the harness to the frame sections.
3. Plug the license plate 2-way flat connector into your trailer light electrical connector.  
*Note: If you do not have a 4-way flat connector on your vehicle, an adapter may be needed. Adapters can be found on the StowAway2.com website or at a local automotive parts stores. Note: A 2-way flat, instead of a 4-way flat, is used on the Sport license plate wire harness because only two wires are needed for operation. This connector will plug directly in your 4-way connector.*
4. To install your license plate on the assembly: slide the two nuts into the plastic groove on the backside of the assembly. Next, position your license plate on the assembly and thread the two machine screws into the nuts (you may have to nudge the nuts to the inside or the outside to enable the screws to line up). Lightly tighten the machine screws with a Phillips screwdriver. To test the license plate light simply turn on your vehicle's running lights – it should be illuminated when these lights are on.